



电气特性参数/ELECTRICAL PARAMETER

相数/NO. OF PHASES	2
步距角/STEP ANGLE	18° ±5%
电压/RATED VOLTAGE	2.45 V
电流/RATED CURRENT	0.35 A
电阻/RESISTANCE	7 ohm±10% AT 20° C
电感/INDUCTANCE	3.17 mH±20% AT 1kHz, 1Vrms
静转矩/HOLDING TORQUE	0.5 N.cm以上/MIN.
定位转矩/DETENT TORQUE	0.2 N.cm以下/Max
绝缘等级/INSULATION CLASS	Class E
引出线规格/LEAD STYLE	AWG28 UL1061

备注/(NOTE):

D				
C				
B				
A	2020.6.20			Van
版本 REV.	年月日 DATE	变更番号 BCN.	变更内容 REVISIONS	设计 BY
设计/DESIGNED	Van	2020.6.20	型号 MODEL	20P020L0-2435
审核/CHECKED	ANDY	2020.6.20		L15.2-1.2-14.5
工艺/TECHNICS			编码 CODE	
批准/APPROVED				

技术部  
2022.09.08  
张建伟

CONNECTOR PIN LOCATION							
PIN NO	COLOR	CCW ← (SEEN FROM FLANGE SIDE) → CW				PHASE	
1	YELLOW	ON	ON		ON	A	
2	BLACK			ON	ON	$\bar{A}$	
3	WHITE		ON	ON		B	
4	RED	ON			ON	$\bar{B}$	

  

技术规格书 TECHNICAL SPECIFICATION		安科特电机有限公司 www.act-motor.com.cn	
一般公差 TOLERANCE	±0.3/±0.3°		
比例 SCALE	2:1	三视图 THIRD ANGLE PROJECTION	
单位 UNIT	mm		
页 SHEET	1/1		