



电机接线图
MOTOR WIRING DIAGRAM



从安装面看为顺时针方向
CLOCKWISE VIEW FROM MOUNTING SIDE

霍尔接线图
HALL WIRING DIAGRAM



霍尔传感器电源电压+5至+20 VDC
HALL SENSOR POWER SUPPLY
VOLTAGE +5 TO +20 VDC

电气特性参数/ELECTRICAL PARAMETER

相数/NO. OF PHASES	3	备注/(NOTE):
标称电压/NOMINAL VOLTAGE	24 VDC	
电阻/ PH-PH RESISTANCE	3.0 Ohm±10% AT 20° C	
空载转速/NO LOAD SPEED	3000±10% RPM	
额定转速/RATED SPEED	2500±10% RPM	
额定转矩/RATED TORQUE	0.057 N.m	
额定输出功率/RATED OUTPUT POWER	15 W	
反电动势常数/BACK EMF CONSTANT	7.75 V/kRPM	
转矩常数/TORQUE CONSTANT	0.074 N.m/A	
电机引出线规格/MOTOR LEAD STYLE	AWG20 UL1015	
霍尔引出线规格/HALL LEAD STYLE	AWG26 UL1007	
绝缘等级/INSULATION CLASS	CLASS B	
绝缘耐压/DIELECTRIC STRENGTH	500V A.C 1分钟/MINUTE	
绝缘电阻/INSULATION RESISTANCE	100 MΩ 以上/MIN.	

				技术规格书 TECHNICAL SPECIFICATION	常州安科特电机有限公司 www.act-motor.com.cn			
B	2022.09.08	—	翻新		JIN	一般公差 TOLERANCE	±0.3/±0.3°	
A	2018.10.27	—	初版	Hahm	比例 SCALE			1:1
版本 REV.	年月日 DATE	变更番号 ECN.	变更内容 REVISIONS	设计 BY	单位 UNIT	mm	页 SHEET	1/1
设计/DESIGNED				Hahm	2018.10.27			
审核/CHECKED				ANDY	2018.10.27		编码 CODE	
工艺/TECHNICS								
批准/APPROVED								

